RIGID CULTIVATOR

Advantages

- It is suitable for use in stone and root obstructed soils and hard black soils.
- Robust and durable main frame constructed of heavy duty tubular as well as angle sections.
- Suitable for inter-culture operations by adjusting the distance between the tynes as per crop requirement.
- It can break hard soil efficiently, uproot stubble to leave the ground perfectly worked and fuel economy.
- It saves time and quality in work as it is easy to operate and quick to adjust.

Model	SKHDRC-9	SKHDRC-11
Number of Tynes	9	11
Tyne profile size (mm)	20, 22 (T) | 25, 28 (T)	20, 22 (T) | 25, 28 (T)
Type of mounting	3 Point Linkage	3 Point Linkage
3 point linkage (mm)	65 x 23 Front | 65 x 16 Front 50 x 12 Rear | 50 x 16 Rear	65 x 12 Front | 65 x 16 Front 50 x 12 Rear | 50 x 16 Rear
Length (mm)	1960	2400
Width (mm)	457	457
Height (mm)	432	432
Cutting width (inch)	9	9
Shovel Thk (mm)	8 (En45)	8 (En45)
Weight (kgs.) approx.	160 - 190 | 200-260	210 - 225 | 235 - 285
Tractor Power HP	35 - 45 | 35 - 45	50 - 70 | 50 - 70